

Ideally, the programming language best suited for the task at hand will be selected. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. It is usually easier to code in "high-level" languages than in "low-level" ones. Integrated development environments (IDEs) aim to integrate all such help. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Scripting and breakpointing is also part of this process. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Different programming languages support different styles of programming (called programming paradigms). It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages.