

It is usually easier to code in "high-level" languages than in "low-level" ones. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Programs were mostly entered using punched cards or paper tape. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Many applications use a mix of several languages in their construction and use. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Integrated development environments (IDEs) aim to integrate all such help. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Use of a static code analysis tool can help detect some possible problems. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Following a consistent programming style often helps readability. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Programmable devices have existed for centuries. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. It is very difficult to determine what are the most popular modern programming languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line.