

Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Unreadable code often leads to bugs, inefficiencies, and duplicated code. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Programs were mostly entered using punched cards or paper tape. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Programs were mostly entered using punched cards or paper tape. Code-breaking algorithms have also existed for centuries. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. It is very difficult to determine what are the most popular modern programming languages. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Programmable devices have existed for centuries. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Programs were mostly entered using punched cards or paper tape. One approach popular for requirements analysis is Use Case analysis.