

The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. There are many approaches to the Software development process. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Also, specific user environment and usage history can make it difficult to reproduce the problem. Programs were mostly entered using punched cards or paper tape. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Integrated development environments (IDEs) aim to integrate all such help. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. There exist a lot of different approaches for each of those tasks. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Programming languages are essential for software development. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Integrated development environments (IDEs) aim to integrate all such help.