

The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. One approach popular for requirements analysis is Use Case analysis. Programming languages are essential for software development. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Many applications use a mix of several languages in their construction and use. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. There exist a lot of different approaches for each of those tasks. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Scripting and breakpointing is also part of this process. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances.