

Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Scripting and breakpointing is also part of this process. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Following a consistent programming style often helps readability. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Scripting and breakpointing is also part of this process. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Different programming languages support different styles of programming (called programming paradigms). Also, specific user environment and usage history can make it difficult to reproduce the problem. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Programming languages are essential for software development.