

By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. It affects the aspects of quality above, including portability, usability and most importantly maintainability. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Code-breaking algorithms have also existed for centuries. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Following a consistent programming style often helps readability. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Following a consistent programming style often helps readability. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). There are many approaches to the Software development process. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). They are the building blocks for all software, from the simplest applications to the most sophisticated ones.