

Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Techniques like Code refactoring can enhance readability. There exist a lot of different approaches for each of those tasks. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Normally the first step in debugging is to attempt to reproduce the problem. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Code-breaking algorithms have also existed for centuries. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Code-breaking algorithms have also existed for centuries. Code-breaking algorithms have also existed for centuries. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly.