

Code-breaking algorithms have also existed for centuries. Different programming languages support different styles of programming (called programming paradigms). For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Normally the first step in debugging is to attempt to reproduce the problem. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Different programming languages support different styles of programming (called programming paradigms). Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Use of a static code analysis tool can help detect some possible problems. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Many applications use a mix of several languages in their construction and use. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Also, specific user environment and usage history can make it difficult to reproduce the problem. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Techniques like Code refactoring can enhance readability.