

Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Scripting and breakpointing is also part of this process. It affects the aspects of quality above, including portability, usability and most importantly maintainability. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Integrated development environments (IDEs) aim to integrate all such help. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Computer programmers are those who write computer software. Integrated development environments (IDEs) aim to integrate all such help. Normally the first step in debugging is to attempt to reproduce the problem. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Many applications use a mix of several languages in their construction and use. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'.