

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Use of a static code analysis tool can help detect some possible problems. Integrated development environments (IDEs) aim to integrate all such help. Programming languages are essential for software development. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Programming languages are essential for software development. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Integrated development environments (IDEs) aim to integrate all such help. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Programming languages are essential for software development. Normally the first step in debugging is to attempt to reproduce the problem. Computer programmers are those who write computer software. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute.