

Scripting and breakpointing is also part of this process. One approach popular for requirements analysis is Use Case analysis. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Also, specific user environment and usage history can make it difficult to reproduce the problem. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Ideally, the programming language best suited for the task at hand will be selected. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. It is usually easier to code in "high-level" languages than in "low-level" ones. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Allen Downey, in his book How To Think Like A Computer Scientist, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams.