

He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Whatever the approach to development may be, the final program must satisfy some fundamental properties. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Unreadable code often leads to bugs, inefficiencies, and duplicated code. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Programmable devices have existed for centuries. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. It is usually easier to code in "high-level" languages than in "low-level" ones. Use of a static code analysis tool can help detect some possible problems. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. One approach popular for requirements analysis is Use Case analysis. Unreadable code often leads to bugs, inefficiencies, and duplicated code. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems.