

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. It affects the aspects of quality above, including portability, usability and most importantly maintainability. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Integrated development environments (IDEs) aim to integrate all such help. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Many applications use a mix of several languages in their construction and use. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Computer programmers are those who write computer software. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Many applications use a mix of several languages in their construction and use. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA.