

In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. There are many approaches to the Software development process. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. It is usually easier to code in "high-level" languages than in "low-level" ones. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. There are many approaches to the Software development process. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Different programming languages support different styles of programming (called programming paradigms). When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Ideally, the programming language best suited for the task at hand will be selected. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Allen Downey, in his book How To Think Like A Computer Scientist, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'.