

New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Also, specific user environment and usage history can make it difficult to reproduce the problem. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Different programming languages support different styles of programming (called programming paradigms). Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Integrated development environments (IDEs) aim to integrate all such help. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Integrated development environments (IDEs) aim to integrate all such help. Programming languages are essential for software development. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. There are many approaches to the Software development process. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Techniques like Code refactoring can enhance readability.