

Computer programmers are those who write computer software. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Programming languages are essential for software development. Normally the first step in debugging is to attempt to reproduce the problem. One approach popular for requirements analysis is Use Case analysis. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Following a consistent programming style often helps readability. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. There are many approaches to the Software development process. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Different programming languages support different styles of programming (called programming paradigms). He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Techniques like Code refactoring can enhance readability. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers.