

It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Ideally, the programming language best suited for the task at hand will be selected. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. It is usually easier to code in "high-level" languages than in "low-level" ones. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications.