

Programmable devices have existed for centuries. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. There exist a lot of different approaches for each of those tasks. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Ideally, the programming language best suited for the task at hand will be selected. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Unreadable code often leads to bugs, inefficiencies, and duplicated code. However, readability is more than just programming style. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Code-breaking algorithms have also existed for centuries. It is usually easier to code in "high-level" languages than in "low-level" ones. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. However, readability is more than just programming style. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Computer programmers are those who write computer software. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years.