

It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Normally the first step in debugging is to attempt to reproduce the problem. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Ideally, the programming language best suited for the task at hand will be selected. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Programs were mostly entered using punched cards or paper tape. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Code-breaking algorithms have also existed for centuries.