

Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Normally the first step in debugging is to attempt to reproduce the problem. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Normally the first step in debugging is to attempt to reproduce the problem. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. It affects the aspects of quality above, including portability, usability and most importantly maintainability. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. Normally the first step in debugging is to attempt to reproduce the problem. Programmable devices have existed for centuries. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation.