

Whatever the approach to development may be, the final program must satisfy some fundamental properties. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Computer programmers are those who write computer software. Integrated development environments (IDEs) aim to integrate all such help. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Different programming languages support different styles of programming (called programming paradigms). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. It is usually easier to code in "high-level" languages than in "low-level" ones. There are many approaches to the Software development process. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Computer programmers are those who write computer software. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Also, specific user environment and usage history can make it difficult to reproduce the problem. Also, specific user environment and usage history can make it difficult to reproduce the problem.