

For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Programs were mostly entered using punched cards or paper tape. Ideally, the programming language best suited for the task at hand will be selected. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Computer programmers are those who write computer software. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Whatever the approach to development may be, the final program must satisfy some fundamental properties. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Programs were mostly entered using punched cards or paper tape. Techniques like Code refactoring can enhance readability. It is usually easier to code in "high-level" languages than in "low-level" ones. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years.