

Programs were mostly entered using punched cards or paper tape. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Code-breaking algorithms have also existed for centuries. Programmable devices have existed for centuries. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Ideally, the programming language best suited for the task at hand will be selected. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. It affects the aspects of quality above, including portability, usability and most importantly maintainability. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Use of a static code analysis tool can help detect some possible problems. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Normally the first step in debugging is to attempt to reproduce the problem. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear.