

Whatever the approach to development may be, the final program must satisfy some fundamental properties. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Ideally, the programming language best suited for the task at hand will be selected. Ideally, the programming language best suited for the task at hand will be selected. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Also, specific user environment and usage history can make it difficult to reproduce the problem. Unreadable code often leads to bugs, inefficiencies, and duplicated code. There exist a lot of different approaches for each of those tasks. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability.