

The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). It is usually easier to code in "high-level" languages than in "low-level" ones. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Programming languages are essential for software development. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Programs were mostly entered using punched cards or paper tape. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. It is very difficult to determine what are the most popular modern programming languages. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Use of a static code analysis tool can help detect some possible problems. It is very difficult to determine what are the most popular modern programming languages. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language.