

Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Integrated development environments (IDEs) aim to integrate all such help. It is usually easier to code in "high-level" languages than in "low-level" ones. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Normally the first step in debugging is to attempt to reproduce the problem. Ideally, the programming language best suited for the task at hand will be selected. Ideally, the programming language best suited for the task at hand will be selected. One approach popular for requirements analysis is Use Case analysis. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Many applications use a mix of several languages in their construction and use. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Also, specific user environment and usage history can make it difficult to reproduce the problem. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. It is usually easier to code in "high-level" languages than in "low-level" ones. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). However, Charles Babbage had already written his first program for the Analytical Engine in 1837.