

FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Different programming languages support different styles of programming (called programming paradigms). Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Programmable devices have existed for centuries. There exist a lot of different approaches for each of those tasks. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Programs were mostly entered using punched cards or paper tape. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Techniques like Code refactoring can enhance readability. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Following a consistent programming style often helps readability. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research.