

The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. It is usually easier to code in "high-level" languages than in "low-level" ones. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Scripting and breakpointing is also part of this process. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Whatever the approach to development may be, the final program must satisfy some fundamental properties. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Whatever the approach to development may be, the final program must satisfy some fundamental properties. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. It affects the aspects of quality above, including portability, usability and most importantly maintainability. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Whatever the approach to development may be, the final program must satisfy some fundamental properties. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm.