Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Programmable devices have existed for centuries. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. There are many approaches to the Software development process. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Programmable devices have existed for centuries. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). One approach popular for requirements analysis is Use Case analysis. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language.