

This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Normally the first step in debugging is to attempt to reproduce the problem. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. There are many approaches to the Software development process. Programs were mostly entered using punched cards or paper tape. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Ideally, the programming language best suited for the task at hand will be selected. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. However, readability is more than just programming style. Techniques like Code refactoring can enhance readability. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference.