

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Normally the first step in debugging is to attempt to reproduce the problem. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Normally the first step in debugging is to attempt to reproduce the problem. It is usually easier to code in "high-level" languages than in "low-level" ones. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). There are many approaches to the Software development process. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Following a consistent programming style often helps readability. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. It affects the aspects of quality above, including portability, usability and most importantly maintainability. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics.