

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Ideally, the programming language best suited for the task at hand will be selected. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Techniques like Code refactoring can enhance readability. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Programming languages are essential for software development. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Scripting and breakpointing is also part of this process. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process.