

He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Many applications use a mix of several languages in their construction and use. Different programming languages support different styles of programming (called programming paradigms). Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. It is very difficult to determine what are the most popular modern programming languages. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Integrated development environments (IDEs) aim to integrate all such help. It is usually easier to code in "high-level" languages than in "low-level" ones. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Programmable devices have existed for centuries. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Integrated development environments (IDEs) aim to integrate all such help. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. However, readability is more than just programming style.