

When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Programmable devices have existed for centuries. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. It is usually easier to code in "high-level" languages than in "low-level" ones. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Also, specific user environment and usage history can make it difficult to reproduce the problem. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Use of a static code analysis tool can help detect some possible problems. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Scripting and breakpointing is also part of this process. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic.