

However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Use of a static code analysis tool can help detect some possible problems. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. Following a consistent programming style often helps readability. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Normally the first step in debugging is to attempt to reproduce the problem. Ideally, the programming language best suited for the task at hand will be selected. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Computer programmers are those who write computer software. Normally the first step in debugging is to attempt to reproduce the problem. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Ideally, the programming language best suited for the task at hand will be selected. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Ideally, the programming language best suited for the task at hand will be selected. Use of a static code analysis tool can help detect some possible problems. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation).