

It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Techniques like Code refactoring can enhance readability. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Code-breaking algorithms have also existed for centuries. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Also, specific user environment and usage history can make it difficult to reproduce the problem. Many applications use a mix of several languages in their construction and use. There exist a lot of different approaches for each of those tasks. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Computer programmers are those who write computer software.