

Ideally, the programming language best suited for the task at hand will be selected. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. It affects the aspects of quality above, including portability, usability and most importantly maintainability. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Normally the first step in debugging is to attempt to reproduce the problem. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Integrated development environments (IDEs) aim to integrate all such help. However, readability is more than just programming style. Programs were mostly entered using punched cards or paper tape. Scripting and breakpointing is also part of this process. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Use of a static code analysis tool can help detect some possible problems. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Programmable devices have existed for centuries. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it.