

Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. It is very difficult to determine what are the most popular modern programming languages. There are many approaches to the Software development process. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. One approach popular for requirements analysis is Use Case analysis. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Also, specific user environment and usage history can make it difficult to reproduce the problem. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Computer programmers are those who write computer software. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process.