

However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Integrated development environments (IDEs) aim to integrate all such help. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). They are the building blocks for all software, from the simplest applications to the most sophisticated ones. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. There are many approaches to the Software development process. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. It is usually easier to code in "high-level" languages than in "low-level" ones.