

Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Programmable devices have existed for centuries. Unreadable code often leads to bugs, inefficiencies, and duplicated code. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Different programming languages support different styles of programming (called programming paradigms). Unreadable code often leads to bugs, inefficiencies, and duplicated code. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Code-breaking algorithms have also existed for centuries. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Scripting and breakpointing is also part of this process. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). It is usually easier to code in "high-level" languages than in "low-level" ones. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Normally the first step in debugging is to attempt to reproduce the problem. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them.