

Normally the first step in debugging is to attempt to reproduce the problem. Following a consistent programming style often helps readability. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Following a consistent programming style often helps readability. Different programming languages support different styles of programming (called programming paradigms). Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA.