

The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Whatever the approach to development may be, the final program must satisfy some fundamental properties. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Normally the first step in debugging is to attempt to reproduce the problem. Programmable devices have existed for centuries. Computer programmers are those who write computer software. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. There are many approaches to the Software development process. There are many approaches to the Software development process. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. There exist a lot of different approaches for each of those tasks. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Use of a static code analysis tool can help detect some possible problems.