

Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). There exist a lot of different approaches for each of those tasks. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. However, readability is more than just programming style. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Many applications use a mix of several languages in their construction and use. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Ideally, the programming language best suited for the task at hand will be selected. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications.