

Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Programmable devices have existed for centuries. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. Also, specific user environment and usage history can make it difficult to reproduce the problem. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. It affects the aspects of quality above, including portability, usability and most importantly maintainability. There are many approaches to the Software development process. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm.