

The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Also, specific user environment and usage history can make it difficult to reproduce the problem. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Also, specific user environment and usage history can make it difficult to reproduce the problem. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Unreadable code often leads to bugs, inefficiencies, and duplicated code. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Also, specific user environment and usage history can make it difficult to reproduce the problem. Computer programmers are those who write computer software. There exist a lot of different approaches for each of those tasks. Integrated development environments (IDEs) aim to integrate all such help.