

Ideally, the programming language best suited for the task at hand will be selected. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Programming languages are essential for software development. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Unreadable code often leads to bugs, inefficiencies, and duplicated code. However, readability is more than just programming style. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. However, readability is more than just programming style. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Different programming languages support different styles of programming (called programming paradigms). It is very difficult to determine what are the most popular modern programming languages. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug.