

The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Use of a static code analysis tool can help detect some possible problems. Normally the first step in debugging is to attempt to reproduce the problem. It is usually easier to code in "high-level" languages than in "low-level" ones. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. It is very difficult to determine what are the most popular modern programming languages. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Different programming languages support different styles of programming (called programming paradigms). A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se.