

How to perform Evil Twin WiFi Attack [Step-by-Step]

WRITTEN BY - KENNEDY MUTHII

Table of Contents

Pre-requisites

Airgeddon

Steps to use Airgeddon to perform Evil Twin WiFi Attack

Step-1: Install Airgeddon

Step-2: Launching airgeddon

Step-3: Choosing an interface to work with

Step-4: Putting the interface on monitor mode

Step-5: Evil twin WiFi attack option

Step-6: Choose the type of attack

Step-7: De-authenticating users and forcing the to connect to the rogue AP

Step-8: Getting the captured passwords

Conclusion

Hello, in this guide we will be launching a captive portal evil twin attack using airgeddon tool. Evil twin attacks have been around for a long time. Attackers combine evil twin attacks and phishing to launch sophisticated social engineering attacks on unsuspecting victims using public hotspots found in cafes and airports. In evil twin attacks, the victim will be redirected to a cloned website requesting his/her credentials.

›

access point. The victim unknowingly connects to the rogue access point. From the rogue access point, the attacker is able to launch phishing attacks.

Pre-requisites

1. Have a **running instance of Kali Linux**.
2. Have a WiFi card that supports both Access Point Creation and monitor mode.
3. Have basic knowledge of the **Linux command line and the commands**.
4. Have a target device. Any type of a device which can connect to an access point. Using another computer or a mobile phone is recommended (***always remember to obtain consent where required before making an attack. Hacking is illegal and is punishable by law***).
5. Have an active internet connection.

ALSO READ:

[Perform a Local File Inclusion Attack \[100% Working\]](#)

Airgeddon

Airgeddon is a Linux command line application with numerous features used by security engineers as they carry out different evil twin attack tests in their day to day work. Some of its features include:

- Interface mode switcher keeping selection even on interface name changing
- Denial of Service over wireless networks using different methods
- Assisted WPA/WPA2 personal networks Handshake file and PMKID capturing
- Cleaning and optimizing Handshake captured files
- Offline password decryption on WPA/WPA2 captured files for personal networks
- Evil Twin attacks (Rogue AP)
- Only Rogue/Fake AP mode to sniff using an external sniffer
- Simple integrated sniffing
- Integrated sniffing, sslstrip2 and BeEF Browser Exploitation Framework (Hostapd + DHCP +

DoS + Bettercap + BeEF)

- Captive portal with "DNS black hole" to capture WiFi passwords
- Optional MAC spoofing for all Evil Twin attacks
- WPS features
- Known WPS PINs attack (bully and reaver), based on online PIN database with auto-update
- Integration of the most common PIN generation algorithms (ComputePIN, EasyBox, Arcadyan, etc.)
- Offline PIN generation and the possibility to search PIN results on a database for a target
- Parameterized timeouts for all attacks
- Enterprise networks attacks
- Fake AP using "smooth" and "noisy" modes capturing enterprise hashes and plain passwords
- Custom certificates creation
- WEP All-in-One attack (combining different techniques: Chop-Chop, Caffe Latte, ARP Replay, Hirte, Fragmentation, Fake association, etc.)

ALSO READ:

[How to disable ICMP timestamp responses in Linux](#)

Steps to use Airedaddon to perform Evil Twin WiFi Attack

Step-1: Install Airedaddon

To install airedaddon, we first download the tool files from [the GitHub repository](#) using the command;

```
git clone https://github.com/v1s1t0r1sh3r3/airgeddon.git
```

Step-2: Launching airedaddon

Before launching an evil twin attack, you have to make sure you have an active internet

›

connection for it is required to install the required dependencies when running airgeddon for the first time. To launch airgeddon, we navigate to the tool's folder we have just downloaded and run using the command as shown in the image below.

```
sudo ./airgeddon.sh
```

Step-3: Choosing an interface to work with

After installing the required dependencies, airgeddon is ready to launch an evil twin attack but first, we need to choose the interface we will be working with. In our case, we will be using **wlan0**. We choose the interface and click enter. ›

Step-4: Putting the interface on monitor mode

Before continuing, we have to put the interface on monitor mode. This will enable us to scan and monitor our target access point. We choose option 2 as shown below.

Step-5: Evil twin WiFi attack option

Now we have airgeddon on monitor mode, our next step to launching an attack is to select the evil twin attack option from where we will select the captive portal option. We will select option 7.

Advertisement

ALSO READ:

[Install Kali Linux Apps on Ubuntu \[100% Working\]](#)

Step-6: Choose the type of attack

>

In attack options, we will choose the evil twin attack with the captive portal option as shown in the image below.

We let it run for some time to detect all the available access point and then close it. After closing, a screen displaying all the detected access points from the screen we select the access point we will attack as shown in the image below.

Step-7: De-authenticating users and forcing the to connect to the rogue AP

On this screen, we need to choose the type of attack we want to launch against the target AP as shown in the image below.

We will choose if we want to run the attack in pursuit mode(Pursuit mode - in some cases, you may find an access point that is set to run in channel hopping mode. This means the access point keeps on switching its channel after a certain period of time. In such a situation, you must use pursuit mode while launching an evil twin attack).

Lastly, we will choose whether to spoof or keep the original mac address.

>

If you want to store the captured handshake file during the evil twin attack, you have to allow it on the next screen as shown below.

ALSO READ:

[Tutorial: Encrypt, Decrypt, Sign a file with GPG Public Key in Linux](#)

We have to select the timeout, but we can leave it at default (20 seconds). Finally, we need to select the language which we will use on the evil twin portal and continue with the attack.

All the users will be de-authenticated from the access point, hence they will try to reconnect to another access point with similar features, this will be our rogue access point. Several screens will appear as shown in the image below. After connecting to the rogue access point, the victim will get redirected to a portal requesting a password as shown in the image below.

Advertisement

Step-8: Getting the captured passwords

On the screen below we are able to see the password that has been submitted by the victim on the portal.

Conclusion

Evil twin attacks have been around for quite some time but still are very successful kinds of attacks. Using public internet access points makes you vulnerable to this kind of attack. When evil twin attacks are combined with phishing attacks, they are very difficult to be detected by a normal person who "just wants to use the internet access point for browsing". Normal users should be taught how to identify such kinds of attacks on them. For aspiring ethical hackers, launching evil twin attacks on the targets is a skill that should be added to your arsenal.

ALSO READ:

[DVWA SQL Injection Exploitation Explained \(Step-by-Step\)](#)



📁 **Ethical hacking**

**Didn't find what you were looking for? Perform a quick search across
GoLinuxCloud**

 

If my articles on **GoLinuxCloud** has helped you, kindly consider buying me a coffee as a token of appreciation.

For any other feedbacks or questions you can either use the [comments section](#) or [contact me](#) form.

Thank You for your support!!

Before you go..

to stay connected and get the latest updates

[Sitemap](#) [Privacy Policy](#) [Disclaimer](#) [Contact](#)

Copyright © 2023 | Hosted On Rocket.net

Leave a Comment

›

Name *

Email *

- ☐ Save my name and email in this browser for the next time I comment.
- ☐ Notify me via e-mail if anyone answers my comment.

Post Comment